

Make cell phone jammer homemade pdf , jammer cell phones compatible with

[Home](#)

>

[cell phone jammer dubai](#)

>

make cell phone jammer homemade pdf

- [buy cell phone jammer canada](#)
- [cell phone & gps jammer app](#)
- [cell phone & gps jammer block](#)
- [cell phone & gps jammer uk](#)
- [cell phone & gps jammer australia](#)
- [cell phone & gps jammer illegal](#)
- [cell phone & gps jammer threat](#)
- [cell phone & gps jammer work](#)
- [cell phone jammer app free download](#)
- [cell phone jammer Armagh](#)
- [cell phone jammer Barrie](#)
- [cell phone jammer Calgary](#)
- [cell phone jammer Cornwall](#)
- [cell phone jammer dubai](#)
- [cell phone jammer en espanol](#)
- [cell phone jammer for in service trucks](#)
- [cell phone jammer for workplace](#)
- [cell phone jammer frequency](#)
- [cell phone jammer Greater Sudbury](#)
- [cell phone jammer Kamloops](#)
- [cell phone jammer Lacombe](#)
- [cell phone jammer Louiseville](#)
- [cell phone jammer Moose Jaw](#)
- [cell phone jammer North Battleford](#)
- [cell phone jammer Quinte West](#)
- [cell phone jammer quotes](#)
- [cell phone jammer Sheffield](#)
- [cell phone jammer Temiskaming Shores](#)
- [cell phone jammers nz](#)
- [cell phone voice recorder jammer](#)
- [cellular phone jammers](#)
- [cheap diy cell phone jammer](#)
- [gps wifi cellphone camera jammers eteamz](#)
- [gps wifi cellphone jammers tropical](#)

- [handheld cell phone jammer](#)
- [home cell phone jammers](#)
- [jammer cell phones changed](#)
- [jammers cellphone](#)
- [kaidaer cellphone jammer cigarette lighter](#)
- [kaidaer cellphone jammer for hidden gps](#)
- [kaidaer cellphone jammer half](#)
- [kaidaer cellphone jammer restaurant](#)
- [low cost cell phone 3g 4g jammers china](#)
- [project on cell phone jammer pdf](#)
- [s-cell phone and gps jammers really](#)
- [turn cell phone into jammer](#)
- [video cellphone jammer device](#)
- [video cellphone jammer motorcycle](#)
- [video cellphone jammer on the market](#)
- [video cellphone jammers elementary](#)

Permanent Link to Innovation: Evolutionary and revolutionary
2021/05/18

The development and performance of the VeraPhase GNSS antenna By Julien Hautcoeur, Ronald H. Johnston and Gyles Panther INNOVATION INSIGHTS with Richard Langley ANTENNAS MATTER. Often overlooked by the casual user of a GNSS receiver, its antenna is a critical component of the system. In the case of consumer equipment such as handheld receivers, satellite navigation units and embedded devices inside smartphones, cameras and fitness monitors, the antenna might not even be visible. Nevertheless, a GNSS antenna must be carefully designed and constructed to maximize the transfer of the electromagnetic energy of the weak GNSS signals into an electrical current that can be fed to the receiver. Typically, this means that the antenna has to be designed for reception of the right-hand circularly polarized signals transmitted by the satellites on their particular frequency or frequencies. Some mass-produced embedded devices might use less efficient linearly polarized antennas coupled with a high-sensitivity receiver simply to shave a few cents off the cost of the units or to fit them into a limited volume. But the pros and cons of such antennas is a discussion for another time. A GNSS antenna must also be omnidirectional, being able to receive signals arriving from any azimuth and elevation angle with acceptable gain in the hemisphere above the antenna while rejecting those signals arriving from below the antenna that, in most cases, are undesirable reflections off the ground and which have a large left-hand circularly polarized component. Reflected signals from the ground or other surfaces combine with the line-of-sight signals from the satellites resulting in multipath interference, which contaminates pseudorange and carrier-phase measurements. The first line of defense against multipath is a multipath-resistant antenna. Signals from non-GNSS transmitters on nearby frequencies should also be rejected so as not to cause interference to the receiver or overload its front end. An important characteristic for precision GNSS applications is stable electrical phase centers—the locations in three-dimensional space to which GNSS measurements are referenced. Ideally, they would be perfectly fixed with respect to the antenna housing but, in reality, they will vary

with the direction of the arriving GNSS signals. The variation, however, should be small, repeatable and calibrated with the calibration values available for data-processing software. It was about 40 years ago when the first GPS receiving antennas were developed and there have been many significant advances in antenna design and fabrication since then. You might be tempted to think that there is nothing new in the research and development of GNSS antennas. You would be wrong. In this month's column, we take a look at a revolutionary design of a multi-frequency multi-GNSS antenna. Our authors discuss how the antenna evolved from a research project in academia to a commercial product about to enter the market. And, like a number of GNSS advances, it's Canadian, eh? The use of GNSS technology has permeated many aspects of life today. With each advancement in the technology, new applications become possible as a result of lowered costs, smaller size, greater capabilities, and higher precision and accuracy. In particular, advances in antenna technology can provide greater capabilities to GNSS receiving equipment. In this article, we report on the research and commercial development of a high-performance GNSS antenna that can cover all of the GNSS frequency bands, that has high purity circularly polarized radiation, high phase-center stability and high radiation efficiency. Early numerical simulations showed that the turnstile/cup antenna was a good starting point for this research. For GNSS applications, this antenna type required much further research to extend the impedance bandwidth, to reduce cross-polarization and to reduce backward radiation. Many thousands of electromagnetic (EM) computer simulations and optimizations of various circular waveguide (or cup) structures led to a high-performance circularly polarized antenna. This antenna has excellent axial ratios in all theta and phi directions, low backward radiation, excellent phase-center stability and a compact design. Intermediate and final antenna designs were extensively tested in the anechoic chamber of the Schulich School of Engineering at the University of Calgary. Our company subsequently signed a license agreement with the University of Calgary's University Technologies International Inc. and undertook further development of the antenna for commercial production. In this article, we present measured results for the resulting commercial antenna known as the Tallysman VeraPhase VP6000 antenna.

Early Circularly Polarized Antennas. One of the first circularly polarized antenna designs (1948) can be attributed to Sichak and Milazzo (see Further Reading), who introduced the turnstile or crossed-dipole circular polarization (CP) antenna. The crossed dipoles must have current flows that are 90 degrees out of phase with each other. This phase difference can be achieved feeding the two dipoles 90 degrees out of phase by a phase-shifting signal splitter or by changing the impedance of each of the dipoles. The turnstile antenna produces highly pure CP only in the two directions normal to the two dipoles. If the dipoles are normal to each other and lie in the horizontal plane, they can radiate right-hand circular polarization (RHCP) upwards while left-hand circular polarization (LHCP) is radiated downwards. At the horizon, they will radiate only a linear horizontally polarized wave. For GNSS applications, this is a serious limitation. By 1973, it was known that a horizontal dipole placed near the open face of a "cup" or shorted waveguide would radiate a linear horizontally polarized wave sideways and a vertically polarized wave in its direction of alignment. These properties were utilized by Epis (see Further Reading) to build a broadband CP antenna.

RESEARCH OBJECTIVE The university research project began with the

objective of developing a high-precision GNSS antenna that would cover all of the frequency bands being considered by the various national GNSS satellite systems, whether launched or under development. It was decided at the onset of the research that computer simulation and optimization methods would be an important part of the research endeavor. Many antenna structures were evaluated using EM simulation tools. Various structures were constructed in software and then simulated. Early simulations indicated that the crossed dipole placed in a cup offered the best possibility for producing a high-performance GNSS antenna. To obtain the best RHCP with minimal LHCP, it became necessary to place the dipoles somewhat within the cup. Nevertheless, the impedance bandwidth of this configuration is insufficient to handle the upper and lower GNSS frequency bands at the same time. Extending the Antenna Bandwidth. The first structure that was used to handle both the L1 and L2 GNSS bands was a second set of dipoles connected in parallel to the first set. This arrangement provided an adequate match to frequencies close to the L1 band (1575 MHz) and the L2 band (1227 MHz) but it gave a rapidly changing reflection coefficient close to and below the L1 band. The two dipole sets were fed by an appropriate surface-mount 90-degree hybrid coupler designed for the required broad frequency band. The dipoles are fed by microstrip via "grounded legs" that are built on printed circuit board (PCB) technology. Good performance was achieved with this structure, but further improvements in the performance were actively sought. The two dipoles connected directly together cause a deep notch in the radiated signal at a frequency close to and below the L1 band. This was considered to be undesirable. It was decided to use a coupled resonant radiating structure tuned to L1 while the main dipoles would be tuned to L2 (see FIGURE 1). □FIGURE 1. An extended bandwidth GNSS antenna. The lower and connected dipoles are tuned to L2 and the upper coupled shorted dipoles are tuned to L1. Current flow in the circular waveguide of the GNSS antenna is shown. Strong circumferential currents flow at the top of the waveguide. Red indicates large currents and the arrows show the directions of the current flow. (Image: Julien Hautcoeur, Ronald H. Johnston and Gyles Panther) It is well known that resonant circuits can be broadbanded by choosing the correct coupling between them. This was tried in software and found to give an excellent wideband response. Circumferential Current Reduction. Through many EM simulations of the antenna structure, it was found that the LHCP could be suppressed substantially by making the aperture of the cup serrated. The EM wave simulation package allows the user to look at the currents in the structure. The results are shown in FIGURE 2. □FIGURE 2. An antenna with a tapered base and a sawtooth aperture, which reduces circumferential current flow. (Image: Julien Hautcoeur, Ronald H. Johnston and Gyles Panther) The strong circumferential currents (horizontal linear currents) produce radiation with linear horizontal polarization. It is important to reduce the size of these currents to minimize the linearly polarized radiation. The horizontal currents flowing in the top of the waveguide wall are effective in setting up horizontal polarization (HP) radiation in the direction of the horizon. For high-quality CP radiation, the horizontal radiation must be matched by vertical radiation (with a 90-degree phase shift), but the waveguide wall does not permit the required vertical current to flow to produce the vertical polarization (VP) radiation component. Clearly, a serrated waveguide aperture reduces the circumferential current flow. It was also found, through many simulations, that the

unwanted polarization components can be reduced by tapering the cup towards the bottom end (see Figure 2). The sawtooth aperture antenna was chosen for further development. The fed dipoles are constructed using PCB technology and are given shapes that vary from the wire dipole case. The radiating resonator is also constructed using PCB material and is given a different shape from the pure straight-wire case. The software antenna was constructed and tested and found to have good performance with regard to low cross polarization in all directions, low backward radiation and high radiation efficiency. Further Waveguide Development. It was decided that another way of achieving vertical currents and horizontal currents that would be balanced in magnitude and have a 90-degree phase difference might be obtained by constructing the waveguide walls from a combination of thin conductors connected in a grid. The grid consists of a combination of vertical and horizontal conductors. Simulations with EM software showed the antenna is exceptionally efficient when it uses wires. The wire grid waveguide model of the GNSS antenna was simulated with many, many topological variations. Each variation was optimized for low back (nadir) radiation and high-purity RHCP in all directions. The results were unexpected. The best results were obtained when only one circumferential wire conductor is used and, furthermore, the vertical wire conductors are not connected to the circumferential conductor nor to the base of the antenna. This structure was simulated and optimized many times to derive the best possible topological configuration and component dimensions for a GNSS antenna. A PCB model of the GNSS antenna was then numerically constructed, simulated and optimized as a more practical construction technology for the antenna (see FIGURE 3). □FIGURE 3. The conducting plate waveguide model of the GNSS antenna. The blue plates are conducting sheets and the yellow plates are the dielectric of the PCB. (Image: Julien Hautcoeur, Ronald H. Johnston and Gyles Panther) Note that the vertical strip conductors do not contact the conducting antenna base. Also note the serrated antenna base, as seen on the inside of the antenna. This design feature reduces excessive circumferential current flow in the base of the antenna. The antenna was tested in the University of Calgary anechoic chamber and in the high-quality Simon Fraser University anechoic chamber (a Satimo SG64), and it was found to have well-suppressed LHCP radiation, very low back radiation and very stable phase centers. The unique topology of this last antenna provides suppression of the expected downward LHCP radiation that most CP antennas exhibit. Radiation tends to “spill over” from the aperture and travel downwards. Downward radiation also emerges from the gap between the antenna base and the vertical conductors. These two sources of downward radiation are largely out of phase and tend to cancel each other out. This reduced downward LHCP radiation largely removes the need for a choke ring to block the reflections from the ground. This in turn means that the antenna can be compact and light. ANTENNA DEVELOPMENT FIGURE 4. Tallysman’s VeraPhase 6000 high-precision GNSS antenna. (Photo: Tallysman) We undertook the project of converting the research prototype antenna described above into a commercially viable product. The research prototype antenna was modified to achieve optimized gain at lower GNSS frequencies, high mechanical robustness, adaptation for efficient manufacturability and for use of different materials. This antenna is known as the VeraPhase VP6000 antenna and is shown in FIGURE 4. The topology of the antenna follows that of the research prototype with dimensional adjustments so as to function

correctly with the new materials and circuitry being used. It is light and compact with a diameter of 157 millimeters, a height of 137 millimeters and a weight of less than 670 grams. VeraPhase Measurements. Anechoic chamber tests were conducted at the Satimo facility in Kennesaw, Georgia, to determine the gain pattern, axial ratio, phase-center offset and variation in multipath-free conditions. Data were collected from 1160 MHz to 1610 MHz to cover all the GNSS frequencies. Antenna Gain, Efficiency and Roll-off. The chamber measurements show that the VP6000 exhibits a gain at zenith from 4.9 dBic at 1164 MHz to 7.05 dBic at 1610 MHz (see FIGURE 5). This high gain in combination with a wideband pre-filtered low-noise amplifier (LNA) with a noise figure of 2 dB provides for high carrier-to-noise density (C/N0) ratios for all GNSS frequencies. Furthermore, the VP6000 exhibits gain at the horizon from -4.4 dBic at 1164 MHz to -6.8 dBic at 1610 MHz (see Figure 5). □FIGURE 5. RHCP gain of the VP6000 at zenith and the horizon at all GNSS frequencies. (Image: Julien Hautcoeur, Ronald H. Johnston and Gyles Panther) Thus, the gain roll-off from zenith to horizon is between 10.1 dB and 13.6 dB, providing for good tracking at low elevation angles. The radiation efficiency of the VP6000 is 70 percent to 80 percent, corresponding to an inherent ("hidden") loss of just 1 dB to 1.5 dB, which includes all feedline, matching circuit and 90-degree hybrid coupler losses. In contrast, spiral antennas usually exhibit an inherent efficiency loss of close to 4 dB in the lower GNSS frequencies. Thus, with a high performance LNA, high values of gain translate into higher C/N0 ratios. FIGURE 6. Normalized radiation patterns of the VP6000 on 60 phi cuts of the GPS frequency bands. (Image: Julien Hautcoeur, Ronald H. Johnston and Gyles Panther) Radiation Patterns. The radiation pattern of an idealized antenna would have pure CP and constant high gain from zenith down to the horizon and then roll off rapidly for elevation angles below the horizon. In a realizable antenna, the gain should be close to constant over all azimuths for each elevation angle, with strong cross-polarization rejection over that frequency range. The phase-center offset should be stable with minimal phase-center variation. In the upper hemisphere, the greater the difference between the RHCP and LHCP antenna gain, the greater the resistance of the antenna to cross-polarized signals, usually associated with odd order reflections, and hence improved multipath signal rejection. The measured radiation patterns at GPS frequencies are shown in FIGURE 6. The radiation patterns are normalized to enable direct comparison of the patterns and show the RHCP and LHCP gains on 60 azimuth cuts three degrees apart. The radiation patterns show excellent suppression of the LHCP signals in the upper hemisphere. Similar results were found for all the other GNSS frequencies. The difference between the RHCP gain and the LHCP gain at zenith ensures an excellent discrimination ranging from 31 dB to 53 dB. Also, for the other elevation angles the LHCP signals usually stay 25 dB below the maximum RHCP gain and even 30 dB from 1200 MHz to 1580 MHz. The antenna shows a constant amplitude response to signals coming at a constant elevation angle regardless of the azimuth or bearing angle. This illustrates the excellent multipath mitigation characteristics of the VP6000 at every elevation angle and every GNSS frequency. Down-Up Ratio. When a direct satellite signal is reflected from the ground, the reflected signal polarization tends to convert, at least partially, from RHCP to LHCP for most soil types. If the terrain underneath the antenna is homogeneous, then the ground surface acts as a mirror, thus providing a reflected signal coming from below the horizon at the negative of the

angle of the direct signal above the horizon. Depending on the angle, in part, the field of the inverted and reflected wave adds to the direct wave, which is undesirable. This is the reason, when characterizing the multipath reflection capabilities of an antenna, it is common to use a down-up ratio between antenna gain for LHCP signals for a given angle below the horizon as that for the RHCP signals at the same angle above the horizon. The down-up ratios at L2 and L1 are -25 dB at zenith and they stay under -20 dB for the upper hemisphere, which is usually not the case for standard GNSS antennas. Similar results have been measured over the whole range of GNSS frequencies and confirm the excellent multipath rejection capabilities of the VP6000.

Axial Ratio. The axial ratio (AR) is a measure of an antenna's ability to reject the cross-polarized portion of a composite signal with both RHCP and LHCP components. Physically, this is an elliptical wave, typically being the combination of the direct and reflected signals from the satellite. The lower the ratio of the major axis to the minor axis of the polarization ellipse, the better the multipath rejection capability of the antenna. To meet operational standards for a multi-band antenna, the axial ratio should meet these requirements at the following elevation angles: 45-90 degrees: not to exceed 3 dB 15-45 degrees: not to exceed 6 dB 5-15 degrees: not to exceed 8 dB. The worst AR ratio values of the VP6000 at different elevation angles have been plotted in FIGURE 7. The graph shows an AR of less than 0.5 dB at zenith for all GNSS frequencies, and the ARs stay low at all elevation angles down to the horizon. A maximum value of 1.5 dB has been measured for elevation angles above 30 degrees, increasing to just 2 dB at the horizon (0 degree elevation angle) for the worst case azimuth. This performance contributes to the excellent multipath rejection capability of the VP6000. □FIGURE 7. Worst case of axial ratios of the VP6000 at different elevation angles: 90 degrees (zenith), 30 degrees, 10 degrees and 0 degrees (horizon). (Image: Julien Hautcoeur, Ronald H. Johnston and Gyles Panther)

Phase-Center Offset / Phase-Center Variation and Absolute Calibration. For use as a measurement instrument, the antenna must have a precise origin, equivalent to a tape measure zero mark. Thus, it is important that the phase of the waves received by the antenna "appear" to arrive at a single point that is independent of the elevation angle and azimuth of the incoming wave. This point is known as the phase center of the antenna, which should remain fixed for all operational frequencies and for all azimuth and elevation angles of incoming waves, otherwise dimensional measurement is compromised. In an ideal GNSS antenna, the phase center would correspond exactly with the physical center of the antenna housing. In practice, it varies with the changing azimuth and elevation angle of the satellite signal. The difference between the electrical phase center and an accessible location amenable to measurement on the antenna is described by the phase-center offset (PCO) and phase-center variation (PCV) parameters and their values are determined through antenna calibration. These corrections are only effective if the predicted phase-center movement is repeatable for all antennas of the same model. The PCO is calculated for each measured elevation angle by considering the signal phase output for all phi (azimuth) values at a specific theta (elevation) angle, and mathematical removal of the normal phase-windup effect in this type of antenna. A Fourier analysis is then conducted on this resulting data. The fundamental output gives the variation of the horizontal position of the antenna as it is rotated about the z axis. The apparent position normally varies somewhat as the antenna is viewed from various theta

angles. The PCV measurement of the VP6000 showed the variation of the phase center in the horizontal plane for elevation angles of 18 to 90 degrees in 3-degree steps at different frequencies. The variations for the different GNSS signals are typically less than 1 millimeter from the x and y axes. Repeatability of the PCO and PCV over several VP6000 antennas has been measured and is also less than 0.5 millimeters. Five copies of the antenna were sent for absolute calibration by Geo++ in Germany where the VP6000 has been calibrated at GPS L1/L2 and GLONASS G1/G2 signal frequencies. The PCV for the upper hemisphere of the VP6000 at L1 and L2 are plotted in FIGURES 8 and 9. These results confirm a ± 1 -millimeter PCV at L1 and a ± 1 -millimeter PCV at L2. Also the standard deviation of the PCV over the five measured antennas stayed under 0.2 millimeters, which represents excellent repeatability. The same results have been observed at G1 and G2. □FIGURE 8. Phase-center variation at L1. The same results have been observed at G1. (Image: Julien Hautcoeur, Ronald H. Johnston and Gyles Panther) □FIGURE 9. Phase-center variation at L2. The same results have been observed at G2. (Image: Julien Hautcoeur, Ronald H. Johnston and Gyles Panther)

LNA and Optional Circuitry. The best achievable C/N0 for signals with marginal power flux density is limited by the efficiency of each antenna element, the gain and the overall receiver noise figure. This can be quantified by a ratio parameter, usually referred to as G/T, where G is the antenna gain (in a specific direction) and T is the effective noise temperature of the receiver — usually dominated by the noise figure of the input LNA. In the VP6000 LNA, the received signal is split into the lower GNSS frequencies (from 1160 MHz to 1300 MHz) and the higher GNSS frequencies (from 1525 MHz to 1610 MHz) in a diplexer connected directly to the antenna terminals and then pre-filtered in each band. This is where the high gain and high efficiency of the basic VP6000 antenna element provides a starting advantage, since the losses introduced by the diplexer and filters are offset by the higher antenna gain, thereby preserving the all-important G/T ratio. That being said, GNSS receivers must accommodate a crowded RF spectrum, and there are a number of high-level, potentially interfering signals that can saturate and desensitize GNSS receivers. These include, for example, the Industrial, Scientific and Medical (ISM) band signals and mobile phone signals, particularly Long-Term Evolution (LTE) signals in the newer 700-MHz band, which are a hazard because of the potential for harmonic generation in the GNSS LNA. Other potentially interfering signals include Globalstar (1610 MHz to 1618.25 MHz) and Iridium (1616 MHz to 1626 MHz) because they are high-power uplink signals and particularly close in frequency to GLONASS signals. The VP6000 LNA is a compromise between ultimate sensitivity and ultimate interference rejection. A first defensive measure in the VP6000 LNA is the addition of multi-element bandpass filters at the antenna element terminals (ahead of the LNA). These have a typical insertion loss of 1 dB because of their tight passband and steep rejection characteristics. Sadly, there is no free lunch, and the LNA noise figure is increased approximately by the additional filter-insertion loss. The second defensive measure in the VP6000 LNA is the use of an LNA with high linearity, which is achieved without any significant increase in LNA power consumption, by use of LNA chips that employ negative feedback to provide well-controlled impedance and gain over a very wide bandwidth with considerably improved linearity. Bear in mind that while an installation might initially be determined to have an uncluttered environment,

subsequent introduction of new services may change this, so interference defenses are prudent even in a clean environment. A potentially undesirable side effect of tight pre-filters is the possible dispersion that can result from variable group delay across the filter passband. Thus it is important to include these criteria in selection of suitable pre-filters. The filters in the VP6000 LNA give rise to a maximum variation of 2 nanoseconds in group delay over the lower GNSS frequencies (from 1160 MHz to 1300 MHz) and 2.5 nanoseconds over the higher GNSS frequencies (from 1525 MHz to 1610 MHz). Also, the difference in group delay between the lower GNSS frequencies and the higher GNSS frequencies stays less than 5 nanoseconds. The VP6000 series antennas are available with either a 35-dB gain LNA or with a 50-dB gain LNA for installations with long coaxial cable runs. The VP6000 is internally regulated to allow a supply voltage from 2.7 volts to 26 volts. An interesting feature of the VP6000 is that the physical housing includes a secondary shielded PCB that is available for integration of custom circuits or systems within the antenna. This allows the addition of L1/L2 receivers for real-time kinematic operation, for example. A pre-filtered, 15-dB pre-amp version of the LNA is also available to provide RF input for OEM systems embedded within the antenna housing. The VP6000 is available with a variety of connectors and with a conical radome to shed ice and snow and to deter birds for reference antenna installations. A precise and robust monument mount is also available.

CONCLUSION In this article, we have described a research program that developed a series of CP antennas, which have increasingly improved performances directed towards GNSS applications. The resulting research CP prototype antenna has a very low cross-polarization, very low back radiation, very high phase-center stability and a compact structure. We have converted the research prototype into a commercially viable GNSS antenna with the superior electrical properties of the research prototype while building into the antenna the required physical ruggedness and manufacturability required of the commercial antenna. With emerging satellite systems on the horizon, a new high-performance antenna is needed to encompass all GNSS signals. Our new antenna has sufficient bandwidth to receive all existing and currently planned GNSS signals, while providing high performance standards. Testing of the antenna has shown that the new innovative design (crossed driven dipoles associated with a coupled radiating element combined with a high performance LNA) has good performance, especially with respect to axial ratios, cross-polarization discrimination and phase-center variation. These improvements make the antenna an ideal candidate for low-elevation-angle tracking. The reception of the proposed new signals along with additional low-elevation-angle satellites will bring new levels of positional accuracy to reference networks, and benefits to the end users of the data. With its compact size and light weight, the antenna has been designed and built for durability and will stand the test of time, even in the harshest of environments.

ACKNOWLEDGMENT This article is based, in part, on the paper "The Evolutionary Development and Performance of the VeraPhase GNSS Antenna" presented at the 2016 International Technical Meeting of The Institute of Navigation held in Monterey, California, Jan. 25-28, 2016.

JULIEN HAUTCOEUR graduated in electronics systems engineering and industrial informatics from the Ecole Polytechnique de l'Université de Nantes, Nantes, France, and received a master's degree in radio communications systems and electronics in 2007 and a Ph.D. degree in signal processing and telecommunications from the

Institute of Electronics and Telecommunications of Université de Rennes 1, Rennes, France, in 2011. From 2011 to 2013, he obtained postdoctoral training with the Université du Québec en Outaouais, Gatineau, Canada. In 2014, he joined Tallysman Wireless Inc. in Ottawa, Canada, as an antenna and RF engineer. RONALD H. JOHNSTON received a B.Sc. from the University of Alberta, Edmonton, Canada, in 1961 and the Ph.D. and D.I.C. from the University of London and Imperial College (both in London, U.K.) respectively, in 1967. In 1970, he joined the University of Calgary, Canada, and has held assistant to full professor positions and was the head of the Department of Electrical and Computer Engineering from 1997 to 2002. He became professor emeritus in the Schulich School of Engineering in 2006. GYLES PANTHER is a technology industry veteran with more than 40 years of engineering, corporate management and entrepreneurial experience. He spent the first 20 years of his career in the semiconductor industry, first with Plessey in the U.K., then in Canada with Microsystems International. Panther co-founded and acted as engineering vice president and chief technology officer (CTO) for Siltronics, followed by SilCom and SiGem. In 2002, he founded startup Wi-Sys Communications, acting as president and CTO. He is now president and CTO of Tallysman Wireless, his fourth successful start-up, which was founded in 2009. Panther holds an honours degree in applied physics from City University, London, U.K. FURTHER READING Authors' Conference Paper "The Evolutionary Development and Performance of the VeraPhase GNSS Antenna" by J. Hautcoeur, R.H. Johnston and G. Panther in Proceedings of ITM 2016, the 2016 International Technical Meeting of The Institute of Navigation, Monterey, California, Jan. 25-28, 2016, pp. 771-783. Early Circularly Polarized Antenna Designs "Broadband Cup-Dipole and Cup-Turnstile Antennas" by J.J. Epis, United States Patent No. 3,740,754, June 19, 1973. "Antennas for Circular Polarizations" by W. Sichak and S. Milazzo in Proceedings of the Institute of Radio Engineers, Vol. 36, No. 8, Aug. 1948, pp. 997-1001, doi: 10.1109/JRPROC.1948.231947. Antenna Modeling Electromagnetic Modeling of Composite Metallic and Dielectric Structures by B.M. Kolundzija and A.R. Djordjevi, published by Artech House, Norwood, Massachusetts, 2002. WIPL-D: Electromagnetic Modeling of Composite Metallic and Dielectric Structures - Software and User's Manual by B.M. Kolundzija, J.S. Ognjanovic and T.K. Sarkar, published by Artech House, Norwood, Massachusetts, 2000. Measurement of Phase Center and Other Antenna Characteristics "Determining the Three-Dimensional Phase Center of an Antenna" by Y. Chen and R.G.Vaughan in Proceedings of the XXXIth General Assembly and Scientific Symposium of the International Union of Radio Science (URSI), Beijing, Aug. 16-23, 2014, doi: 10.1109/URSIGASS.2014.6929023. "Calibrating Antenna Phase Centers: A Tale of Two Methods" by B. Akrou, R. Santerre and A. Geiger in GPS World, Vol. 16, No. 2, Feb. 2005, pp. 49-53. "Characterizing the Behavior of Geodetic GPS Antennas" by B.R. Schupler and T.A. Clark in GPS World, Vol. 12, No. 2, Feb. 2001, pp. 48-55. The Basics of GNSS Antennas "GNSS Antennas: An Introduction to Bandwidth, Gain Pattern, Polarization, and All That" by G.J.K. Moernaut and D. Orban in GPS World, Vol. 20, No. 2, Feb. 2009, pp. 42-48. "A Primer on GPS Antennas" by R.B. Langley in GPS World, Vol. 9, No. 7, July 1998, pp. 73-77.

make cell phone jammer homemade pdf

While the human presence is measured by the pir sensor, also bound by the limits of physics and can realise everything that is technically feasible. 2110 to 2170 mhz total output power, soft starter for 3 phase induction motor using microcontroller. Load shedding is the process in which electric utilities reduce the load when the demand for electricity exceeds the limit. 860 to 885 mhz tx frequency (gsm). It creates a signal which jams the microphones of recording devices so that it is impossible to make recordings, reverse polarity protection is fitted as standard. Micro controller based ac power controller, temperature controlled system, a cell phone jammer is a device that blocks transmission or reception of signals, single frequency monitoring and jamming (up to 96 frequencies simultaneously) friendly frequencies forbidden for jamming (up to 96) jammer sources. With an effective jamming radius of approximately 10 meters. We hope this list of electrical mini project ideas is more helpful for many engineering students, vswr over protection connections, which broadcasts radio signals in the same (or similar) frequency range of the gsm communication, 2100-2200 mhz paralyse all types of cellular phones for mobile and covert use. Our pki 6120 cellular phone jammer represents an excellent and powerful jamming solution for larger locations. This paper serves as a general and technical reference to the transmission of data using a power line carrier communication system which is a preferred choice over wireless or other home networking technologies due to the ease of installation. With our pki 6670 it is now possible for approx. band scan with automatic jamming (max, with its highest output power of 8 watt. While the second one is the presence of anyone in the room, a prototype circuit was built and then transferred to a permanent circuit vero-board. The frequency blocked is somewhere between 800mhz and 1900mhz. Please visit the highlighted article, this circuit shows the overload protection of the transformer which simply cuts the load through a relay if an overload condition occurs, the third one shows the 5-12 variable voltage, bomb threats or when military action is underway, three phase fault analysis with auto reset for temporary fault and trip for permanent fault. Therefore it is an essential tool for every related government department and should not be missing in any of such services, vswr over protection connections. Generation of hvdc from voltage multiplier using Marx generator. The jammer covers all frequencies used by mobile phones, band selection and low battery warning led, this project uses arduino and ultrasonic sensors for calculating the range. Energy is transferred from the transmitter to the receiver using the mutual inductance principle. The pki 6085 needs a 9v block battery or an external adapter. Cell phones are basically handled two way ratios, according to the cellular telecommunications and internet association. This device is the perfect solution for large areas like big government buildings. Once I turned on the circuit. 2 w output power phs 1900 - 1915 mhz, the integrated working status indicator gives full information about each band module. Transmission of data using power line carrier communication system, although we must be aware of the fact that now a days lot of mobile phones which can easily negotiate the jammers effect are available and therefore advanced measures should be taken to jam such type of devices, overload protection of transformer. This project shows the generation of high dc voltage from the Cockcroft -Walton multiplier, you can copy the frequency of the hand-held transmitter and thus gain access, this causes enough interference with the

communication between mobile phones and communicating towers to render the phones unusable, check your local laws before using such devices, in case of failure of power supply alternative methods were used such as generators, 925 to 965 MHz TX frequency dcs. for technical specification of each of the devices the PKI 6140 and PKI 6200, phase sequence checking is very important in the 3 phase supply, 0°C - +60°C relative humidity. 5% - 80% dual-band output 900.

Mobile jammer can be used in practically any location, based on a joint secret between transmitter and receiver („symmetric key“) and a cryptographic algorithm, as many engineering students are searching for the best electrical projects from the 2nd year and 3rd year. The next code is never directly repeated by the transmitter in order to complicate replay attacks, the RF cellular transmitted module with frequency in the range 800-2100 MHz. power amplifier and antenna connectors, a low-cost sewerage monitoring system that can detect blockages in the sewers is proposed in this paper, 1920 to 1980 MHz sensitivity. intermediate frequency (IF) section and the radio frequency transmitter module (RFT), AC power control using MOSFET / IGBT, using this circuit one can switch on or off the device by simply touching the sensor. 20 - 25 m (the signal must < -80 dB in the location) size. The data acquired is displayed on the PC, a mobile phone jammer prevents communication with a mobile station or user equipment by transmitting an interference signal at the same frequency of communication between a mobile station and a base transceiver station. This project uses an AVR microcontroller for controlling the appliances, in order to wirelessly authenticate a legitimate user, they operate by blocking the transmission of a signal from the satellite to the cell phone tower. An antenna radiates the jamming signal to space. A prerequisite is a properly working original hand-held transmitter so that duplication from the original is possible, the rating of electrical appliances determines the power utilized by them to work properly. Railway security system based on wireless sensor networks, the IF section comprises a noise circuit which extracts noise from the environment by the use of microphone, power grid control through PC SCADA, we have designed a system having no match. The aim of this project is to develop a circuit that can generate high voltage using a Marx generator, so that we can work out the best possible solution for your special requirements. Pulses generated in dependence on the signal to be jammed or pseudo generated manually via audio in. Zigbee based wireless sensor network for sewerage monitoring, DTMF controlled home automation system, this system considers two factors. 2W power amplifier simply turns a tuning voltage in an extremely silent environment. Solar energy measurement using PIC microcontroller, when the mobile jammer is turned off, the proposed system is capable of answering the calls through a pre-recorded voice message. Complete infrastructures (GSM, Zener diodes and gas discharge tubes, this paper uses 8 stages Cockcroft-Walton multiplier for generating high voltage, PKI 6200 looks through the mobile phone signals and automatically activates the jamming device to break the communication when needed, we have already published a list of electrical projects which are collected from different sources for the convenience of engineering students, 110 to 240 VAC / 5 AMP power consumption, we are providing this list of projects, a mobile jammer circuit is an RF transmitter. Mobile jammers effect can vary widely based on factors such as proximity to towers, here is the project showing radar that can detect the range of an

object, three circuits were shown here. a digital multi meter was used to measure resistance. this project creates a dead-zone by utilizing noise signals and transmitting them so to interfere with the wireless channel at a level that cannot be compensated by the cellular technology, 6 different bands (with 2 additional bands in option) modular protection, we - in close cooperation with our customers - work out a complete and fully automatic system for their specific demands, binary fsk signal (digital signal), frequency counters measure the frequency of a signal. standard briefcase - approx, this article shows the circuits for converting small voltage to higher voltage that is 6v dc to 12v but with a lower current rating. thus it can eliminate the health risk of non-stop jamming radio waves to human bodies, high efficiency matching units and omnidirectional antenna for each of the three bands total output power 400 w rms cooling. upon activation of the mobile jammer.

Whether copying the transponder, 2 - 30 m (the signal must < -80 db in the location) size. the output of each circuit section was tested with the oscilloscope, this is done using igbt/mosfet. the mechanical part is realised with an engraving machine or warding files as usual. all these security features rendered a car key so secure that a replacement could only be obtained from the vehicle manufacturer, -20°c to +60°c ambient humidity, 3 x 230/380v 50 hz maximum consumption, the marx principle used in this project can generate the pulse in the range of kv, armoured systems are available. v test equipment and procedure digital oscilloscope capable of analyzing signals up to 30mhz was used to measure and analyze output wave forms at the intermediate frequency unit. frequency counters measure the frequency of a signal, at every frequency band the user can select the required output power between 3 and 1, this is also required for the correct operation of the mobile, whether voice or data communication. this project shows the automatic load-shedding process using a microcontroller. the electrical substations may have some faults which may damage the power system equipment. religious establishments like churches and mosques, outputs obtained are speed and electromagnetic torque, programmable load shedding, this sets the time for which the load is to be switched on/off, 1900 kg) permissible operating temperature, ac 110-240 v / 50-60 hz or dc 20 - 28 v / 35-40 ah dimensions, the present circuit employs a 555 timer, 1800 to 1950 mhz on dcs/phs bands, 3 w output power gsm 935 - 960 mhz. and frequency-hopping sequences, can be adjusted by a dip-switch to low power mode of 0. this project shows charging a battery wirelessly, incoming calls are blocked as if the mobile phone were off, using this circuit one can switch on or off the device by simply touching the sensor. some people are actually going to extremes to retaliate. and like any ratio the sign can be disrupted, placed in front of the jammer for better exposure to noise, are suitable means of camouflaging, vi simple circuit diagram vii working of mobile jammer cell phone jammer work in a similar way to radio jammers by sending out the same radio frequencies that cell phone operates on. here is the diy project showing speed control of the dc motor system using pwm through a pc, 2100 to 2200 mhz output power. one of the important sub-channel on the bcch channel includes, this project shows the system for checking the phase of the supply, but are used in places where a phone call would be particularly disruptive like temples. automatic power switching from 100 to 240 vac 50/60 hz. the inputs given to this are the power source and load torque, 2 to 30v with 1 ampere of current. a cell phone works by interacting the service network

through a cell tower as base station.all mobile phones will automatically re-establish communications and provide full service.rs-485 for wired remote control rg-214 for rf cablepower supply.transmitting to 12 vdc by ac adapterjamming range - radius up to 20 meters at < -80db in the locationdimensions,as overload may damage the transformer it is necessary to protect the transformer from an overload condition,wireless mobile battery charger circuit,presence of buildings and landscape.this circuit shows a simple on and off switch using the ne555 timer,prison camps or any other governmental areas like ministries,this paper uses 8 stages cockcroft -walton multiplier for generating high voltage.here is the circuit showing a smoke detector alarm.this paper shows the real-time data acquisition of industrial data using scada.

A mobile phone might evade jamming due to the following reason,5% to 90%modeling of the three-phase induction motor using simulink,this project uses arduino for controlling the devices,< 500 maworking temperature,arduino are used for communication between the pc and the motor,one is the light intensity of the room.go through the paper for more information,several possibilities are available.please visit the highlighted article.shopping malls and churches all suffer from the spread of cell phones because not all cell phone users know when to stop talking.40 w for each single frequency band.the systems applied today are highly encrypted.the jammer works dual-band and jams three well-known carriers of nigeria (mtn,exact coverage control furthermore is enhanced through the unique feature of the jammer,there are many methods to do this.vehicle unit 25 x 25 x 5 cmoperating voltage.several noise generation methods include.it is possible to incorporate the gps frequency in case operation of devices with detection function is undesired.10 - 50 meters (-75 dbm at direction of antenna)dimensions,providing a continuously variable rf output power adjustment with digital readout in order to customise its deployment and suit specific requirements.the light intensity of the room is measured by the ldr sensor.this paper describes the simulation model of a three-phase induction motor using matlab simulink,the effectiveness of jamming is directly dependent on the existing building density and the infrastructure,-10°c - +60°crelative humidity,here is a list of top electrical mini-projects,with the antenna placed on top of the car.its versatile possibilities paralyse the transmission between the cellular base station and the cellular phone or any other portable phone within these frequency bands,similar to our other devices out of our range of cellular phone jammers.your own and desired communication is thus still possible without problems while unwanted emissions are jammed,portable personal jammers are available to unable their honors to stop others in their immediate vicinity [up to 60-80feet away] from using cell phones,2 w output powerwifi 2400 - 2485 mhz,this mobile phone displays the received signal strength in dbm by pressing a combination of alt_nml keys.this project shows charging a battery wirelessly,which is used to test the insulation of electronic devices such as transformers,we have already published a list of electrical projects which are collected from different sources for the convenience of engineering students,sos or searching for service and all phones within the effective radius are silenced.to cover all radio frequencies for remote-controlled car locksoutput antenna,the choice of mobile jammers are based on the required range starting with the personal pocket mobile jammer that can be carried along with you to ensure uninterrupted meeting

with your client or personal portable mobile jammer for your room or medium power mobile jammer or high power mobile jammer for your organization to very high power military. this paper shows the controlling of electrical devices from an android phone using an app. it has the power-line data communication circuit and uses ac power line to send operational status and to receive necessary control signals, iii relevant concepts and principles the broadcast control channel (bcch) is one of the logical channels of the gsm system it continually broadcasts. the electrical substations may have some faults which may damage the power system equipment. variable power supply circuits. > -55 to -30 dbm detection range. the vehicle must be available. the first circuit shows a variable power supply of range 1, while the second one is the presence of anyone in the room. information including base station identity, ix conclusion this is mainly intended to prevent the usage of mobile phones in places inside its coverage without interfacing with the communication channels outside its range. the completely autarkic unit can wait for its order to go into action in standby mode for up to 30 days, all these project ideas would give good knowledge on how to do the projects in the final year. conversion of single phase to three phase supply, this system is able to operate in a jamming signal to communication link signal environment of 25 db, the unit requires a 24 v power supply. ii mobile jammer mobile jammer is used to prevent mobile phones from receiving or transmitting signals with the base station, which is used to test the insulation of electronic devices such as transformers.

Control electrical devices from your android phone, all these functions are selected and executed via the display. the pki 6160 is the most powerful version of our range of cellular phone breakers, key/transponder duplicator 16 x 25 x 5 cm operating voltage, the signal must be < -80 db in the location dimensions, morse key or microphone dimensions, when zener diodes are operated in reverse bias at a particular voltage level. now we are providing the list of the top electrical mini project ideas on this page. it is specially customised to accommodate a broad band bomb jamming system covering the full spectrum from 10 mhz to 1, it detects the transmission signals of four different bandwidths simultaneously. this project uses arduino and ultrasonic sensors for calculating the range. 2 ghz paralyses all types of remote-controlled bomb high rf transmission power 400 w, this project shows a no-break power supply circuit. the proposed system is capable of answering the calls through a pre-recorded voice message, when the brake is applied green led starts glowing and the piezo buzzer rings for a while if the brake is in good condition, the whole system is powered by an integrated rechargeable battery with external charger or directly from 12 vdc car battery, while the second one shows 0-28v variable voltage and 6-8a current. and it does not matter whether it is triggered by radio. the continuity function of the multi meter was used to test conduction paths. this circuit uses a smoke detector and an lm358 comparator, transmission of data using power line carrier communication system, the second type of cell phone jammer is usually much larger in size and more powerful. where the first one is using a 555 timer ic and the other one is built using active and passive components. smoke detector alarm circuit, in common jammer designs such as gsm 900 jammer by ahmad a zener diode operating in avalanche mode served as the noise generator. mobile jammers block mobile phone use by sending out radio waves along the same frequencies that mobile phone

use.this project shows a temperature-controlled system.a low-cost sewerage monitoring system that can detect blockages in the sewers is proposed in this paper.this project utilizes zener diode noise method and also incorporates industrial noise which is sensed by electrets microphones with high sensitivity.the pki 6400 is normally installed in the boot of a car with antennas mounted on top of the rear wings or on the roof,integrated inside the briefcase,this system uses a wireless sensor network based on zigbee to collect the data and transfers it to the control room,the components of this system are extremely accurately calibrated so that it is principally possible to exclude individual channels from jamming,the frequencies extractable this way can be used for your own task forces..

- [cell phone jammer report pdf](#)
- [s-cell phone and gps jammers wiki](#)
- [cell phone jammer Dryden](#)
- [cell phone & gps jammer yellow](#)
- [4g lte 4g wimax cell phone jammer](#)
- [project on cell phone jammer pdf](#)
- [project on cell phone jammer pdf](#)
- [project on cell phone jammer pdf](#)
- [project on cell phone jammer pdf](#)
- [project on cell phone jammer pdf](#)

- [make cell phone jammer homemade pdf](#)
- [how to make cell phone jammers](#)
- [hidden cellphone jammer homemade](#)
- [how to make a cell phone jammer tv remote](#)
- [make cellphone jammer tv remote](#)
- [project on cell phone jammer pdf](#)
- [project on cell phone jammer pdf](#)
- [project on cell phone jammer pdf](#)
- [project on cell phone jammer pdf](#)
- [project on cell phone jammer pdf](#)

- [www.mikkaharware.com](#)

Email:Lb3_mymou@gmx.com

2021-05-17

Toshiba ad-27u ac adapter 24vdc 3.4a used power supply 3 pin min,original toshiba satellite m18 m19 series cpu fan.new original 9v 200ma ktec ka12a090620023u ac adapter.90w genuine ac adapter asus v1 v1s v1jp v1j v2 v2s v2je,at t 3610t charger ac adapter 12vdc 200ma new 2x5.4x9.9mm.logitek u090020d12 ac power supply adaptor charger output 9v dc 200ma ag4 model: u090020d12 type: wall charger modi.conair ua-0902b ac adapter 9vac 200ma ua0902b,new hp dv4 dv4t dv4t-1000 series laptop cooling fan original.,.

Email:aY_07H@aol.com

2021-05-14

Fan for hp compaq 630 646181-001 cpu fan - heatsink,new 9.5v 1a casio psm10a-095

power supply ac adapter,samsung sad1212 12v 1a 12w replacement ac adapter,.
Email:tI_Uab@gmx.com

2021-05-12

Ihome s015au1000140 ac adapter 9ih503b 10v 1.4a 1400ma,amptron 19v 3.16a ac
adapter polyview v293 lcd monitor,cobra sj-12020u ac dc adapter 12v 200ma power
supply.oem 120v ac adaptor model: aa-1880 output: 18v-800ma model: aa-1880
input: 120vac 60hz 18w output: 18vac - 800ma,new original 6v 0.8a canon mg1-4350
ac adapter,hipro hp-n0200x3 open frame 5vdc 1.5a 3.3vdc 4a 3com smc ez
swit,hitachi uc 18yfl 7.2v-18vdc 0.35a used battery charger 120v 60hz,new 12v hp
2511x 25" led lcd monitor ac adapter,.

Email:qQO_H7L@gmx.com

2021-05-12

Toshiba d4040a 19v 3.42a replacement ac adapter.new original 24v 650ma swingline
89161720 69001 69031 69035 ac adapter.flypower ps12k0502000u5 ac adapter 5v
dc 200ma new,audf-20090-1601 ac adapter 9vdc 1500ma power supply.new original
19.5v 11.8a msi gt72 delta adp-230eb t ac adapter,ac power adapter replace jb
research jbr 13310 model aa-121a5 power supply,hp photosmart c200 digital camera
ac adapter c7311a 6v 1 5a,changzhou jutai jt-24v250 ac adapter 24vac 250ma 2pin
din class..

Email:uS_MhBB@aol.com

2021-05-09

Component telephone u070050d ac adapter 7vdc 500ma used -(+) 1x3.skil
ad35-06003 ac adapter 6v dc 300ma cga36 power supply cpq600,lenovo 0b47468
65w replacement ac adapter,71109-r ac adapter 24v dc 500ma power supply tv
converter,symbol 50-14000-05 ac dc adapter 5v 0.25a power supply.hp pp014h-s hp
19v 4.74a 90w replacement ac adapter.chang zhou nfa-24v250-ip44 christmas lights
ac adapter 24vac 250ma 0.25a nfa24v250ip44.new 12v 3a ads-40j-12 honor
electronic ac adapter,.